Vinilprimer E 29

(Provisional)

Description

VINILPRIMER E 29 is a primer for plasticized or rigid PVC films. It is based on a balanced blend of synthetic, natural elastomers and resin dispersions, properly stabilized and compounded.

Application

VINILPRIMER E 29 allows to obtain a perfect adhesion between the adhesive mass (based on natural or synthetic rubbers) and the PVC film, without curing.
It is mainly used for self-adhesive tapes and films, either for packaging or technical use.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	29±1
3. Brookfield Viscosity 25°C	mPa.s	50 - 150 (1)
8. pH		8 - 10
Solvents		water

(1) No 1 RV; 20 RPM

Handling

The product can be diluted to a lower viscosity.
Thickening: if necessary, with usual acrylic thickeners.
Application: 1.0 - 1.5 g dry/sqm. Stir before usage anche check pH value, it must be between 8 and 10 (if necessary, add ammonia).

Packaging

The product is supplied in iron drums (200 kg); IBC containers (1000 kg).

Storing

This product must be stored at a temperature between +10 and +40°C.
PROTECT FROM FREEZING

Use within 6 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it