Vinilsol 10

Description

VINILSOL 10 is a solvent borne primer for PVC pressure sensitive tapes.
It consist of a balanced rubber and resin formulation designed to achieve very good adhesion between PVC film (rigid/plasticized) and rubber based adhesives.

Technical Specifications

Method of analysis	MU	Standard
1. Total Solids	%	10±1
3. Brookfield Viscosity 25°C	mPa.s	50 - 200 (1)
Solvents		toluene / MEK

(1) No 1 RV; 50 RPM

Handling

VINILSOL 10 must be well stirred before usage.
Coat approx. 10 - 12 g wet/sqm of VINILSOL 10, by Mayer-bar or reverse roll or rotogravure. Before coating, a crosslinker must be added to the product: add 1 to 1.5 pp of a suitable isocyanate to 100 parts of VINILSOL 10, suggested crosslinker are our CURING AGENT RF/AEDE or CURING AGENT D.

Pot-life will be reduced, as crosslinking mechanism starts immedialtely after the addition of isocyanate.

Packaging

The product is supplied in iron drums (170 kg).

Storing

Store in a fresh and ventilated area, far from direct sunlight and heat sources. Keep containers well closed to prevent solvent evaporation.

Use within 12 months from production date (unopened and in the original packaging).

Build date 11 Sep 2025

Above information is reliable, but does not constitute warranty.

ICHEMCO srl
via 11 Settembre, 5 - 20012 CUGGIONO (MI) - ITALY
Phone: +39 02 97243.1 - info@ichemco.it - www.ichemco.it